

FRESH

SILVER DECO

**A+/A
19dB**
Z09EM / Z12EM / E18EM
**A++/A+
19dB**
P24EL

**5
AÑOS
Garantía**

389 €
399 €

			Z09EM.SSW E09EM.UA3	Z12EM.SSW E12EM.UA3	E18EM.SSM E18EM.UL2	P24EL.SS2 P24EL.NS2
			Z09EM.NSW	Z12EM.NSH	E18EM.NSM	P24EL.UUE
Interior			Interior			
Exterior			Exterior			
Capacidad (min.-nom.-máx.)	Refrigeración	W	890 / 2500 / 3700	900 / 3500 / 4040	900 / 5000 / 5400	900 / 6800 / 7420
	Calefacción	W	890 / 3200 / 4100	890 / 3800 / 5100	900 / 5400 / 6100	900 / 8000 / 8640
	Calefacción -7°C	W	3000	3600	3800	4850
Consumo	Refrigeración	W	730	1.120	1.720	2.193
	Calefacción +7°C	W	950	1.040	1.540	2.285
EER	W/W		3,42	3,13	2,91	3,10
S.E.E.R			5,7	5,8	5,3	6,1
P design Refrigeración	Kw		2,5	3,5	5,0	6,8
COP	W/W		3,37	3,65	3,51	3,50
SCOP			3,8	3,8	3,8	3,8
P design Calefacción	Kw		2,3	3,2	3,8	5,5
Etiqueta Energética	Frío / Calor		A+ / A	A+ / A	A / A	A++ / A+
Consumo anual de energía	Frío / Calor	kWh	154 / 847	211 / 1179	330 / 1400	391 / 2027
Presión sonora (S/B/M/A)	Refrigeración	dB(A)	20 / 25 / 33 / 39	20 / 25 / 33 / 39	29 / 35 / 40 / 42	29 / 35 / 40 / 45
	Calefacción	dB(A)	28 / 33 / 39	28 / 33 / 39	35 / 40 / 42	35 / 40 / 45
Caudal de aire (S/B/M/A/max)	Refrigeración	m ³ /min	3 / 4,5 / 6 / 7,5 / 9	3,5 / 5,5 / 8 / 10 / 12	8 / 10,5 / 13 / 15 / 19	8 / 11 / 14 / 15 / 23
	Calefacción	m ³ /min	5 / 6 / 8	6,5 / 8 / 10	10,5 / 13 / 15	11,5 / 15 / 18,5
Alimentación eléctrica	Φ / V / Hz		1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50	1 / 220-240 / 50
Cable alimentación	N x mm ²		3 x 1.0	3 x 1.0	3 x 1.5	3 x 2.5
Cable interconexión	N x mm ²		4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)	4 x 0.75 (Including Earth)	4 x 1.0 (Including Earth)
Dimensiones	mm		756*265*184	798*292*214	885*296*236	1090*330*248
Peso neto	kg		7,4	8,5	9,5	14
Exterior			Exterior			
Rango operación	Refrigeración	°CDB	-10-48	-10-48	-10-48	-10-48
	Calefacción	°CWB	-10-24	-10-24	-10-24	-10-24
Presión sonora	Refrigeración	dB(A)	49	49	52	54
	Calefacción	dB(A)	49	49	54	54
Caudal de aire		m ³ /min	27	27	32	50
Límites longitud tuberías	Total	Mín.	3	3	-	-
		Máx.	15	15	20	30
	Altura Máxima	m	7	7	10	15
Conexiones frigoríficas	Líquido	mm	6,35	6,35	6,35	6,35
		pulg.	(1/4)	(1/4)	(1/4)	(1/4)
	Gas	mm	9,52	9,52	12,7	15,88
		pulg.	(3/8)	(3/8)	(1/2)	(5/8)
	Drenaje	mm	21,5	21,5	21,5	21,5
		pulg.	0,85	0,85	0,85	0,85
Refrigerante	Tipo		R410A	R410A	R410A	R410A
	Carga a 7.5 m	g	850	900	1050	1350
	Carga adicional	g/m	20	20	20	35
Compresor			Rotary	Rotary	Rotary	Twin Rotary
Peso neto	kg		28	28	34	46
Dimensiones	mm		717 x 483 x 230	717 x 483 x 230	770 x 545 x 288	870 x 655 x 320